

---

# Sakila Sample Database

## Table of Contents

1. Preface and Legal Notices .....	1
2. Introduction .....	2
3. History .....	3
4. Installation .....	3
5. Structure .....	5
5.1. Tables .....	7
5.2. Views .....	12
5.3. Stored Procedures .....	13
5.4. Stored Functions .....	15
5.5. Triggers .....	17
6. Usage Examples .....	17
7. Acknowledgments .....	19
8. License for the Sakila Sample Database .....	19
9. Note for Authors .....	19
10. Sakila Change History .....	19
10.1. Version 0.8 .....	19
10.2. Version 0.7 .....	20
10.3. Version 0.6 .....	20
10.4. Version 0.5 .....	20
10.5. Version 0.4 .....	20
10.6. Version 0.3 .....	20
10.7. Version 0.2 .....	21

This document describes the Sakila sample database—its history, installation, structure and usage.

For legal information, see the [Legal Notices](#).

Document generated on: 2013-01-28 (revision: 34053)

## 1. Preface and Legal Notices

This document describes the Sakila sample database—its history, installation, structure and usage.

### Legal Notices

Copyright © 2007, 2011, Oracle and/or its affiliates. All rights reserved.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this software or related documentation is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, the following notice is applicable:

U.S. GOVERNMENT RIGHTS Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are "commercial computer software" or "commercial technical data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, duplication, disclosure, modification, and adaptation shall be subject to the restrictions and license terms set forth in the applicable Government

contract, and, to the extent applicable by the terms of the Government contract, the additional rights set forth in FAR 52.227-19, Commercial Computer Software License (December 2007). Oracle USA, Inc., 500 Oracle Parkway, Redwood City, CA 94065.

This software is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications which may create a risk of personal injury. If you use this software in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure the safe use of this software. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software in dangerous applications.

Oracle is a registered trademark of Oracle Corporation and/or its affiliates. MySQL is a trademark of Oracle Corporation and/or its affiliates, and shall not be used without Oracle's express written authorization. Other names may be trademarks of their respective owners.

This software and documentation may provide access to or information on content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.

This document in any form, software or printed matter, contains proprietary information that is the exclusive property of Oracle. Your access to and use of this material is subject to the terms and conditions of your Oracle Software License and Service Agreement, which has been executed and with which you agree to comply. This document and information contained herein may not be disclosed, copied, reproduced, or distributed to anyone outside Oracle without prior written consent of Oracle or as specifically provided below. This document is not part of your license agreement nor can it be incorporated into any contractual agreement with Oracle or its subsidiaries or affiliates.

This documentation is NOT distributed under a GPL license. Use of this documentation is subject to the following terms:

You may create a printed copy of this documentation solely for your own personal use. Conversion to other formats is allowed as long as the actual content is not altered or edited in any way. You shall not publish or distribute this documentation in any form or on any media, except if you distribute the documentation in a manner similar to how Oracle disseminates it (that is, electronically for download on a Web site with the software) or on a CD-ROM or similar medium, provided however that the documentation is disseminated together with the software on the same medium. Any other use, such as any dissemination of printed copies or use of this documentation, in whole or in part, in another publication, requires the prior written consent from an authorized representative of Oracle. Oracle and/or its affiliates reserve any and all rights to this documentation not expressly granted above.

For more information on the terms of this license, or for details on how the MySQL documentation is built and produced, please visit [MySQL Contact & Questions](#).

For help with using MySQL, please visit either the [MySQL Forums](#) or [MySQL Mailing Lists](#) where you can discuss your issues with other MySQL users.

For additional documentation on MySQL products, including translations of the documentation into other languages, and downloadable versions in variety of formats, including HTML and PDF formats, see the [MySQL Documentation Library](#).

## 2. Introduction

The Sakila sample database was developed by Mike Hillyer, a former member of the MySQL AB documentation team, and is intended to provide a standard schema that can be used for examples in books, tutorials, articles, samples, and so forth. Sakila sample database also serves to highlight the latest features of MySQL such as Views, Stored Procedures, and Triggers.

Additional information on the Sakila sample database and its usage can be found through the [MySQL forums](#).

The Sakila sample database is the result of support and feedback from the MySQL user community and feedback and user input is always appreciated. Please direct all feedback using the <http://www.mysql.com/company/contact/>. For bug reports, use [MySQL Bugs](#).

### 3. History

The Sakila sample database was designed as a replacement to the `world` sample database, also provided by MySQL AB.

The `world` sample database provides a set of tables containing information on the countries and cities of the world and is useful for basic queries, but lacks structures for testing MySQL-specific functionality and new features found in MySQL 5.

Development of the Sakila sample database began in early 2005. Early designs were based on the database used in the Dell whitepaper [Three Approaches to MySQL Applications on Dell PowerEdge Servers](#).

Where Dell's sample database was designed to represent an online DVD store, the Sakila sample database is designed to represent a DVD rental store. The Sakila sample database still borrows film and actor names from the Dell sample database.

Development was accomplished using MySQL Query Browser for schema design, with the tables being populated by a combination of MySQL Query Browser and custom scripts, in addition to contributor efforts (see [Section 7, "Acknowledgments"](#)).

After the basic schema was completed, various views, stored routines, and triggers were added to the schema; then the sample data was populated. After a series of review versions, the first official version of the Sakila sample database was released in March 2006.

### 4. Installation

The Sakila sample database is available from <http://dev.mysql.com/doc/index-other.html>. A downloadable archive is available in compressed `tar` file or Zip format. The archive contains three files: `sakila-schema.sql`, `sakila-data.sql`, and `sakila.mwb`.

The `sakila-schema.sql` file contains all the `CREATE` statements required to create the structure of the Sakila database including tables, views, stored procedures, and triggers.

The `sakila-data.sql` file contains the `INSERT` statements required to populate the structure created by the `sakila-schema.sql` file, along with definitions for triggers that must be created after the initial data load.

The `sakila.mwb` file is a MySQL Workbench data model that you can open within MySQL Workbench to examine the database structure. For more information, see [MySQL Workbench](#).

To install the Sakila sample database, follow these steps:

1. Extract the installation archive to a temporary location such as `C:\temp\` or `/tmp/`. When you unpack the archive, it creates a directory named `sakila-db` that contains the `sakila-schema.sql` and `sakila-data.sql` files.
2. Connect to the MySQL server using the `mysql` command-line client with the following command:

```
shell> mysql -u root -p
```

Enter your password when prompted. A non-`root` account can be used as long as the account has privileges to create new databases.

3. Execute the `sakila-schema.sql` script to create the database structure by using the following command:

```
mysql> SOURCE C:/temp/sakila-db/sakila-schema.sql;
```

Replace `C:/temp/sakila-db` with the path to the `sakila-schema.sql` file on your system.

**Note**

On Windows you should use slashes, rather than backslashes, when executing the `SOURCE` command.

- Execute the `sakila-data.sql` script to populate the database structure with the following command:

```
mysql> SOURCE C:/temp/sakila-db/sakila-data.sql;
```

Replace `C:/temp/sakila-db` with the path to the `sakila-data.sql` file on your system.

- Confirm that the sample database is installed correctly. Execute the following statements. You should see output similar to that shown here.

```
mysql> USE sakila;
Database changed


mysql> SHOW TABLES;
+-----+
| Tables_in_sakila |
+-----+
| actor             |
| address           |
| category          |
| city              |
| country           |
| customer          |
| customer_list     |
| film              |
| film_actor        |
| film_category     |
| film_list         |
| film_text         |
| inventory         |
| language          |
| nicer_but_slower_film_list |
| payment           |
| rental            |
| sales_by_film_category |
| sales_by_store    |
| staff             |
| staff_list        |
| store             |
+-----+
22 rows in set (0.00 sec)

mysql> SELECT COUNT(*) FROM film;
+-----+
| COUNT(*) |
+-----+
| 1000     |
+-----+
1 row in set (0.02 sec)

mysql> SELECT COUNT(*) FROM film_text;
+-----+
| COUNT(*) |
+-----+
| 1000     |
+-----+
1 row in set (0.00 sec)
```

## 5. Structure

The following diagram provides an overview of the structure of the Sakila sample database. The diagram source file (for use with MySQL Workbench) is included in the Sakila distribution and is named [sakila.mwb](#).



## 5.1. Tables

The following sections describe the tables that make up the Sakila sample database, in alphabetic order.

### 5.1.1. The actor Table

The `actor` table lists information for all actors.

The `actor` table is joined to the `film` table by means of the `film_actor` table.

#### Columns

- `actor_id`: A surrogate primary key used to uniquely identify each actor in the table.
- `first_name`: The actor's first name.
- `last_name`: The actor's last name.
- `last_update`: The time that the row was created or most recently updated.

### 5.1.2. The address Table

The `address` table contains address information for customers, staff, and stores.

The `address` table primary key appears as a foreign key in the `customer`, `staff`, and `store` tables.

#### Columns

- `address_id`: A surrogate primary key used to uniquely identify each address in the table.
- `address`: The first line of an address.
- `address2`: An optional second line of an address.
- `district`: The region of an address, this may be a state, province, prefecture, etc.
- `city_id`: A foreign key pointing to the `city` table.
- `postal_code`: The postal code or ZIP code of the address (where applicable).
- `phone`: The telephone number for the address.
- `last_update`: The time that the row was created or most recently updated.

### 5.1.3. The category Table

The `category` table lists the categories that can be assigned to a film.

The category table is joined to the `film` table by means of the `film_category` table.

#### Columns

- `category_id`: A surrogate primary key used to uniquely identify each category in the table.
- `name`: The name of the category.
- `last_update`: The time that the row was created or most recently updated.

### 5.1.4. The city Table

The `city` table contains a list of cities.

The `city` table is referred to by a foreign key in the `address` table and refers to the `country` table using a foreign key.

### Columns

- `city_id`: A surrogate primary key used to uniquely identify each city in the table.
- `city`: The name of the city.
- `country_id`: A foreign key identifying the country that the city belongs to.
- `last_update`: The time that the row was created or most recently updated.

### 5.1.5. The country Table

The `country` table contains a list of countries.

The `country` table is referred to by a foreign key in the `city` table.

### Columns

- `country_id`: A surrogate primary key used to uniquely identify each country in the table.
- `country`: The name of the country.
- `last_update`: The time that the row was created or most recently updated.

### 5.1.6. The customer Table

The `customer` table contains a list of all customers.

The `customer` table is referred to in the `payment` and `rental` tables and refers to the `address` and `store` tables using foreign keys.

### Columns

- `customer_id`: A surrogate primary key used to uniquely identify each customer in the table.
- `store_id`: A foreign key identifying the customer's "home store." Customers are not limited to renting only from this store, but this is the store they generally shop at.
- `first_name`: The customer's first name.
- `last_name`: The customer's last name.
- `email`: The customer's email address.
- `address_id`: A foreign key identifying the customer's address in the `address` table.
- `active`: Indicates whether the customer is an active customer. Setting this to `FALSE` serves as an alternative to deleting a customer outright. Most queries should have a `WHERE active = TRUE` clause.
- `create_date`: The date the customer was added to the system. This date is automatically set using a trigger during an `INSERT`.
- `last_update`: The time that the row was created or most recently updated.

### 5.1.7. The film Table

The `film` table is a list of all films potentially in stock in the stores. The actual in-stock copies of each film are represented in the `inventory` table.



The `film` table refers to the `language` table and is referred to by the `film_category`, `film_actor`, and `inventory` tables.

## Columns

- `film_id`: A surrogate primary key used to uniquely identify each film in the table.
- `title`: The title of the film.
- `description`: A short description or plot summary of the film.
- `release_year`: The year in which the movie was released.
- `language_id`: A foreign key pointing at the `language` table; identifies the language of the film.
- `original_language_id`: A foreign key pointing at the `language` table; identifies the original language of the film. Used when a film has been dubbed into a new language.
- `rental_duration`: The length of the rental period, in days.
- `rental_rate`: The cost to rent the film for the period specified in the `rental_duration` column.
- `length`: The duration of the film, in minutes.
- `replacement_cost`: The amount charged to the customer if the film is not returned or is returned in a damaged state.
- `rating`: The rating assigned to the film. Can be one of: `G`, `PG`, `PG-13`, `R`, or `NC-17`.
- `special_features`: Lists which common special features are included on the DVD. Can be zero or more of: `Trailers`, `Commentaries`, `Deleted Scenes`, `Behind the Scenes`.
- `last_update`: The time that the row was created or most recently updated.

### 5.1.8. The `film_actor` Table

The `film_actor` table is used to support a many-to-many relationship between films and actors. For each actor in a given film, there will be one row in the `film_actor` table listing the actor and film.

The `film_actor` table refers to the `film` and `actor` tables using foreign keys.

#### Columns:

- `actor_id`: A foreign key identifying the actor.
- `film_id`: A foreign key identifying the film.
- `last_update`: The time that the row was created or most recently updated.

### 5.1.9. The `film_category` Table

The `film_category` table is used to support a many-to-many relationship between films and categories. For each category applied to a film, there will be one row in the `film_category` table listing the category and film.

The `film_category` table refers to the `film` and `category` tables using foreign keys.

#### Columns:

- `film_id`: A foreign key identifying the film.
- `category_id`: A foreign key identifying the category.

- `last_update`: The time that the row was created or most recently updated.

### 5.1.10. The `film_text` Table

The `film_text` table is the only table in the Sakila sample database that uses the `MyISAM` storage engine. This table is provided to allow for full-text searching of the titles and descriptions of the films listed in the `film` table.

The `film_text` table contains the `film_id`, `title` and `description` columns of the `film` table, with the contents of the table kept in synchrony with the `film` table by means of triggers on the `film` table's `INSERT`, `UPDATE` and `DELETE` operations (see [Section 5.5, "Triggers"](#)).

#### Columns

- `film_id`: A surrogate primary key used to uniquely identify each film in the table.
- `title`: The title of the film.
- `description`: A short description or plot summary of the film.

The contents of the `film_text` table should never be modified directly. All changes should be made to the `film` table instead.

### 5.1.11. The `inventory` Table

The `inventory` table contains one row for each copy of a given film in a given store.

The `inventory` table refers to the `film` and `store` tables using foreign keys and is referred to by the `rental` table.

#### Columns

- `inventory_id`: A surrogate primary key used to uniquely identify each item in inventory.
- `film_id`: A foreign key pointing to the film this item represents.
- `store_id`: A foreign key pointing to the store stocking this item.
- `last_update`: The time that the row was created or most recently updated.

### 5.1.12. The `language` Table

The `language` table is a lookup table listing the possible languages that films can have for their language and original language values.

The `language` table is referred to by the `film` table.

#### Columns

- `language_id`: A surrogate primary key used to uniquely identify each language.
- `name`: The English name of the language.
- `last_update`: The time that the row was created or most recently updated.

### 5.1.13. The `payment` Table

The `payment` table records each payment made by a customer, with information such as the amount and the rental being paid for (when applicable).

The `payment` table refers to the `customer`, `rental`, and `staff` tables.

## Columns

- `payment_id`: A surrogate primary key used to uniquely identify each payment.
- `customer_id`: The customer whose balance the payment is being applied to. This is a foreign key reference to the `customer` table.
- `staff_id`: The staff member who processed the payment. This is a foreign key reference to the `staff` table.
- `rental_id`: The rental that the payment is being applied to. This is optional because some payments are for outstanding fees and may not be directly related to a rental.
- `amount`: The amount of the payment.
- `payment_date`: The date the payment was processed.
- `last_update`: The time that the row was created or most recently updated.

### 5.1.14. The rental Table

The `rental` table contains one row for each rental of each inventory item with information about who rented what item, when it was rented, and when it was returned.

The `rental` table refers to the `inventory`, `customer`, and `staff` tables and is referred to by the `payment` table.

## Columns

- `rental_id`: A surrogate primary key that uniquely identifies the rental.
- `rental_date`: The date and time that the item was rented.
- `inventory_id`: The item being rented.
- `customer_id`: The customer renting the item.
- `return_date`: The date and time the item was returned.
- `staff_id`: The staff member who processed the rental.
- `last_update`: The time that the row was created or most recently updated.

### 5.1.15. The staff Table

The `staff` table lists all staff members, including information on email address, login information, and picture.

The `staff` table refers to the `store` and `address` tables using foreign keys, and is referred to by the `rental`, `payment`, and `store` tables.

## Columns

- `staff_id`: A surrogate primary key that uniquely identifies the staff member.
- `first_name`: The first name of the staff member.
- `last_name`: The last name of the staff member.
- `address_id`: A foreign key to the staff member's address in the `address` table.
- `picture`: A `BLOB` containing a photograph of the employee.

- `email`: The staff member's email address.
- `store_id`: The staff member's "home store". The employee can work at other stores but is generally assigned to the store listed.
- `active`: Whether this is an active employee. If employees leave their rows are not deleted from this table, instead this column is set to `FALSE`.
- `username`: The user name used by the staff member to access the rental system.
- `password`: The password used by the staff member to access the rental system. The password should be stored as a hash using the `SHA1()` function.
- `last_update`: The time that the row was created or most recently updated.

### 5.1.16. The store Table

The `store` table lists all stores in the system. All inventory is assigned to specific stores, and staff and customers are assigned a "home store".

The `store` table refers to the `staff` and `address` tables using foreign keys and is referred to by the `staff`, `customer`, and `inventory` tables.

#### Columns

- `store_id`: A surrogate primary key that uniquely identifies the store.
- `manager_staff_id`: A foreign key identifying the manager of this store.
- `address_id`: A foreign key identifying the address of this store.
- `last_update`: The time that the row was created or most recently updated.

## 5.2. Views

The following sections describe the views that are included with the Sakila sample database, in alphabetic order.

### 5.2.1. The actor\_info View

The `actor_info` view provides a list of all actors, including the films in which they have performed, broken down by category.

The `staff_list` view incorporates data from the `film`, `actor`, `category`, `film_actor`, and `film_category` tables.

### 5.2.2. The customer\_list View

The `customer_list` view provides a list of customers, with first name and last name concatenated together and address information combined into a single view.

The `customer_list` view incorporates data from the `customer`, `address`, `city`, and `country` tables.

### 5.2.3. The film\_list View

The `film_list` view contains a formatted view of the `film` table, with a comma-separated list of the film's actors.

The `film_list` view incorporates data from the `film`, `category`, `film_category`, `actor`, and `film_actor` tables.

### 5.2.4. The `nicer_but_slower_film_list` View

The `nicer_but_slower_film_list` view contains a formatted view of the `film` table, with a comma-separated list of the film's actors.

The `nicer_but_slower_film_list` view differs from the `film_list` view in the list of actors. The lettercase of the actor names is adjusted so that the first letter of each name is capitalized, rather than having the name in all-caps.

As indicated in its name, the `nicer_but_slower_film_list` view performs additional processing and therefore takes longer to return data than the `film_list` view.

The `nicer_but_slower_film_list` view incorporates data from the `film`, `category`, `film_category`, `actor`, and `film_actor` tables.

### 5.2.5. The `sales_by_film_category` View

The `sales_by_film_category` view provides a list of total sales, broken down by individual film category.

Because a film can be listed in multiple categories, it is not advisable to calculate aggregate sales by totalling the rows of this view.

The `sales_by_film_category` view incorporates data from the `category`, `payment`, `rental`, `inventory`, `film`, `film_category`, and `category` tables.

### 5.2.6. The `sales_by_store` View

The `sales_by_store` view provides a list of total sales, broken down by store.

The view returns the store location, manager name, and total sales.

The `sales_by_store` view incorporates data from the `city`, `country`, `payment`, `rental`, `inventory`, `store`, `address`, and `staff` tables.

### 5.2.7. The `staff_list` View

The `staff_list` view provides a list of all staff members, including address and store information.

The `staff_list` view incorporates data from the `staff` and `address` tables.

## 5.3. Stored Procedures

The following sections describe the stored procedures included with the Sakila sample database, in alphabetic order.

All parameters listed are `IN` parameters unless listed otherwise.

### 5.3.1. The `film_in_stock` Stored Procedure

#### Description

The `film_in_stock` stored procedure is used to determine whether any copies of a given film are in stock at a given store.

#### Parameters

- `p_film_id`: The ID of the film to be checked, from the `film_id` column of the `film` table.
- `p_store_id`: The ID of the store to check for, from the `store_id` column of the `store` table.

- `p_film_count`: An *OUT* parameter that returns a count of the copies of the film in stock.

## Return Values

This procedure produces a table of inventory ID numbers for the copies of the film in stock, and returns (in the `p_film_count` parameter) a count that indicates the number of rows in that table.

## Sample Usage

```
mysql> CALL film_in_stock(1,1,@count);
+-----+
| inventory_id |
+-----+
| 1             |
| 2             |
| 3             |
| 4             |
+-----+
4 rows in set (0.06 sec)

Query OK, 0 rows affected (0.06 sec)

mysql> SELECT @count;
+-----+
| @count |
+-----+
| 4      |
+-----+
1 row in set (0.00 sec)
```

## 5.3.2. The `film_not_in_stock` Stored Procedure

### Description

The `film_not_in_stock` stored procedure is used to determine whether there are any copies of a given film not in stock (rented out) at a given store.

### Parameters

- `p_film_id`: The ID of the film to be checked, from the `film_id` column of the `film` table.
- `p_store_id`: The ID of the store to check for, from the `store_id` column of the `store` table.
- `p_film_count`: An *OUT* parameter that returns a count of the copies of the film not in stock.

### Return Values

This procedure produces a table of inventory ID numbers for the copies of the film not in stock, and returns (in the `p_film_count` parameter) a count that indicates the number of rows in that table.

### Sample Usage

```
mysql> CALL film_not_in_stock(2,2,@count);
+-----+
| inventory_id |
+-----+
| 9            |
+-----+
1 row in set (0.02 sec)

Query OK, 0 rows affected (0.02 sec)

mysql> SELECT @count;
+-----+
| @count |
+-----+
| 1      |
+-----+
```

```
+-----+
1 row in set (0.00 sec)
```

### 5.3.3. The `rewards_report` Stored Procedure

#### Description

The `rewards_report` stored procedure generates a customizable list of the top customers for the previous month.

#### Parameters

- `min_monthly_purchases`: The minimum number of purchases or rentals a customer needed to make in the last month to qualify.
- `min_dollar_amount_purchased`: The minimum dollar amount a customer needed to spend in the last month to qualify.
- `count_rewardees`: An `OUT` parameter that returns a count of the customers who met the qualifications specified.

#### Return Values

This function returns a table of customers who met the qualifications specified. The table has the same structure as the `customer` table. The procedure also returns (in the `count_rewardees` parameter) a count that indicates the number of rows in that table.

#### Sample Usage

```
mysql> CALL rewards_report(7,20.00,@count);
...
| 598          | 1          | WADE          | DELVALLE      | WADE.DELVALLE@sakilacustomer.org | 604
| 599          | 2          | AUSTIN        | CINTRON       | AUSTIN.CINTRON@sakilacustomer.org | 605
...
42 rows in set (0.11 sec)

Query OK, 0 rows affected (0.67 sec)

mysql> SELECT @count;
+-----+
| @count |
+-----+
| 42     |
+-----+
1 row in set (0.00 sec)
```

## 5.4. Stored Functions

The following sections describe the stored functions included with the Sakila sample database.

### 5.4.1. The `get_customer_balance` Function

The `get_customer_balance` function returns the current amount owing on a specified customer's account.

#### Parameters

- `p_customer_id`: The ID of the customer to check, from the `customer_id` column of the `customer` table.
- `p_effective_date`: The cutoff date for items that will be applied to the balance. Any rentals, payments, and so forth after this date are not counted.

## Return Values

This function returns the amount owing on the customer's account.

## Sample Usage

```
mysql> SELECT get_customer_balance(298,NOW());
+-----+
| get_customer_balance(298,NOW()) |
+-----+
| 22.00                             |
+-----+
1 row in set (0.00 sec)
```

## 5.4.2. The inventory\_held\_by\_customer Function

The `inventory_held_by_customer` function returns the `customer_id` of the customer who has rented out the specified inventory item.

### Parameters

- `p_inventory_id`: The ID of the inventory item to be checked.

### Return Values

This function returns the `customer_id` of the customer who is currently renting the item, or `NULL` if the item is in stock.

### Sample Usage

```
mysql> SELECT inventory_held_by_customer(8);
+-----+
| inventory_held_by_customer(8) |
+-----+
| NULL                           |
+-----+
1 row in set (0.14 sec)

mysql> SELECT inventory_held_by_customer(9);
+-----+
| inventory_held_by_customer(9) |
+-----+
| 366                             |
+-----+
1 row in set (0.00 sec)
```

## 5.4.3. The inventory\_in\_stock Function

The `inventory_in_stock` function returns a boolean value indicating whether the inventory item specified is in stock.

### Parameters

- `p_inventory_id`: The ID of the inventory item to be checked.

### Return Values

This function returns `TRUE` or `FALSE` to indicate whether the item specified is in stock.

### Sample Usage

```
mysql> SELECT inventory_in_stock(9);
+-----+
| inventory_in_stock(9) |
+-----+
| 0                       |
+-----+
```



```

1 row in set (0.03 sec)

mysql> SELECT inventory_in_stock(8);
+-----+
| inventory_in_stock(8) |
+-----+
| 1                      |
+-----+
1 row in set (0.00 sec)

```

## 5.5. Triggers

The following sections describe the triggers in the Sakila sample database.

### 5.5.1. The `customer_create_date` Trigger

The `customer_create_date` trigger sets the `create_date` column of the `customer` table to the current time and date as rows are inserted.

### 5.5.2. The `payment_date` Trigger

The `payment_date` trigger sets the `payment_date` column of the `payment` table to the current time and date as rows are inserted.

### 5.5.3. The `rental_date` Trigger

The `rental_date` trigger sets the `rental_date` column of the `rental` table to the current time and date as rows are inserted.

### 5.5.4. The `ins_film` Trigger

The `ins_film` trigger duplicates all `INSERT` operations on the `film` table to the `film_text` table.

### 5.5.5. The `upd_film` Trigger

The `upd_film` trigger duplicates all `UPDATE` operations on the `film` table to the `film_text` table.

### 5.5.6. The `del_film` Trigger

The `del_film` trigger duplicates all `DELETE` operations on the `film` table to the `film_text` table.

## 6. Usage Examples

These are a few usage examples of how to perform common operations using the Sakila sample database. While these operations are good candidates for stored procedures and views, such implementation is intentionally left as an exercise to the user.

### Rent a DVD

To rent a DVD, first confirm that the given inventory item is in stock, and then insert a row into the `rental` table. After the `rental` table is created, insert a row into the `payment` table. Depending on business rules, you may also need to check whether the customer has an outstanding balance before processing the rental.

```

mysql> SELECT INVENTORY_IN_STOCK(10);
+-----+
| INVENTORY_IN_STOCK(10) |
+-----+
| 1                      |
+-----+
1 row in set (0.00 sec)

mysql> INSERT INTO rental(rental_date, inventory_id, customer_id, staff_id)

```

```

-> VALUES(NOW(), 10, 3, 1);
Query OK, 1 row affected (0.00 sec)

mysql> SELECT @balance := get_customer_balance(3, NOW());
+-----+
| @balance := get_customer_balance(3, NOW()) |
+-----+
| 4.99 |
+-----+
1 row in set (0.01 sec)

mysql> INSERT INTO payment (customer_id, staff_id, rental_id, amount, payment_date)
-> VALUES(3,1,LAST_INSERT_ID(), @balance, NOW());
Query OK, 1 row affected (0.00 sec)

```

## Return a DVD

To return a DVD, update the `rental` table and set the return date. To do this, first identify the `rental_id` to update based on the `inventory_id` of the item being returned. Depending on the situation, it may be necessary to check the customer balance and perhaps process a payment for overdue fees by inserting a row into the `payment` table.

```

mysql> SELECT rental_id
-> FROM rental
-> WHERE inventory_id = 10
-> AND customer_id = 3
-> AND return_date IS NULL;
+-----+
| rental_id |
+-----+
| 16050 |
+-----+
1 row in set (0.00 sec)

mysql> UPDATE rental
-> SET return_date = NOW()
-> WHERE rental_id = @rentID;
Query OK, 1 row affected (0.00 sec)
Rows matched: 1 Changed: 1 Warnings: 0

mysql> SELECT get_customer_balance(3, NOW());
+-----+
| get_customer_balance(3, NOW()) |
+-----+
| 0.00 |
+-----+
1 row in set (0.09 sec)

```

## Find Overdue DVDs

Many DVD stores produce a daily list of overdue rentals so that customers can be contacted and asked to return their overdue DVDs.

To create such a list, search the `rental` table for films with a return date that is `NULL` and where the rental date is further in the past than the rental duration specified in the `film` table. If so, the film is overdue and we should produce the name of the film along with the customer name and phone number.

```

mysql> SELECT CONCAT(customer.last_name, ' ', customer.first_name) AS customer,
-> address.phone, film.title
-> FROM rental INNER JOIN customer ON rental.customer_id = customer.customer_id
-> INNER JOIN address ON customer.address_id = address.address_id
-> INNER JOIN inventory ON rental.inventory_id = inventory.inventory_id
-> INNER JOIN film ON inventory.film_id = film.film_id
-> WHERE rental.return_date IS NULL
-> AND rental_date + INTERVAL film.rental_duration DAY < CURRENT_DATE()
-> LIMIT 5;
+-----+

```

customer	phone	title
OLVERA, DWAYNE	62127829280	ACADEMY DINOSAUR
HUEY, BRANDON	99883471275	ACE GOLDFINGER
BROWN, ELIZABETH	10655648674	AFFAIR PREJUDICE
OWENS, CARMEN	272234298332	AFFAIR PREJUDICE
HANNON, SETH	864392582257	AFRICAN EGG

5 rows in set (0.02 sec)

## 7. Acknowledgments

The following individuals and organizations have contributed to the development of the Sakila sample database.

- [Roland Bouman](#), certification developer at MySQL AB [Author](#). Provided valuable feedback throughout the development process, contributed sample views and stored procedures.
- [Ronald Bradford](#), [Developer](#) at MySQL AB. Developed [first sample application](#) for use with the Sakila sample database.
- [Dave Jaffe](#), [Dell](#). Provided schema used in Dell whitepaper and secured permission to use parts thereof in the Sakila sample database.
- [Giuseppe Maxia](#), former CTO of [Stardata](#), now QA developer at MySQL AB. Provided valuable feedback throughout the development process, populated some of the sample data, provided some of the sample views and triggers.
- [Jay Pipes](#), [MySQL community advocate](#). Provided some of the sample stored procedures.
- [Zak Greant](#), [Community advocate and author](#). Provided advice and feedback on licensing.

In addition to the individuals mentioned above, various other individuals in MySQL AB and the community have provided feedback during the course of development.

## 8. License for the Sakila Sample Database

The contents of the `sakila-schema.sql` and `sakila-data.sql` files are licensed under the New BSD license.

Information on the New BSD license can be found at <http://www.opensource.org/licenses/bsd-license.php> and [http://en.wikipedia.org/wiki/BSD\\_License](http://en.wikipedia.org/wiki/BSD_License).

The additional materials included in the Sakila distribution, including this documentation, are not licensed under an open license. Use of this documentation is subject to the terms described in [Section 1, "Legal Notices"](#).

Please Contact <http://www.mysql.com/company/contact/> for more information.

## 9. Note for Authors

When using the Sakila sample database for articles and books, it is strongly recommended that you explicitly list the version of the Sakila sample database that is used in your examples. This way readers will download the same version for their use and not encounter any differences in their results that may occur from upgrades to the data or schema.

## 10. Sakila Change History

### 10.1. Version 0.8

- Corrected `upd_film` trigger definition to include changes to `film_id` values.

- Added `actor_info` view.
- Changed error handler for `inventory_held_by_customer` function. Function now has an exit handler for `NOT FOUND` instead of the more cryptic `1329`.
- Added template for new BSD license to schema and data files.
- Added `READS SQL DATA` to the procedures and functions where appropriate to support loading on MySQL 5.1.
- Fixed date-range issue in the `rewards_report` procedure (thanks Goplat).

## 10.2. Version 0.7

- Fixed bug in `sales_by_store` view that caused the same manager to be listed for every store.
- Fixed bug in `inventory_held_by_customer` function that caused function to return multiple rows.
- Moved `rental_date` trigger to `sakila-data.sql` file to prevent it from interfering with data loading.

## 10.3. Version 0.6

- Added `film_in_stock` stored procedure.
- Added `film_not_in_stock` stored procedure.
- Added `inventory_help_by_customer` stored function.
- Added `inventory__in_stock` stored function.
- Optimized data file for loading (multiple-row `INSERT` statements, transactions). (Thanks Giuseppe)
- Fixed error in `payment` table loading script that caused infinitely increasing payment amounts.

## 10.4. Version 0.5

- Added `sales_by_store` and `sales_by_film_category` views, submitted by Jay Pipes.
- Added `rewards_report` stored procedure, submitted by Jay Pipes.
- Added `get_customer_balance` stored procedure.
- Added `sakila-data.sql` file to load data into sample database.

## 10.5. Version 0.4

- Added `password` column to `staff` table (`VARCHAR(40) BINARY DEFAULT NULL`).

## 10.6. Version 0.3

- Changed `address.district` to `VARCHAR(20)`.
- Changed `customer.first_name` to `VARCHAR(45)`.
- Changed `customer.last_name` to `VARCHAR(45)`.
- Changed `customer.email` to `VARCHAR(50)`.
- Added `payment.rental_id` column (an `INT NULL` column).
- Foreign key added for `payment.rental_id` to `rental.rental_id`.

- `rental.rental_id` added, `INT Auto_Increment`, made into surrogate primary key, old primary key changed to `UNIQUE` key.

## 10.7. Version 0.2

- All tables have a `last_update` `TIMESTAMP` column with traditional behavior (`DEFAULT CURRENT_TIMESTAMP ON UPDATE CURRENT_TIMESTAMP`).
- `actor_id` is now a `SMALLINT`.
- `address_id` is now a `SMALLINT`.
- `category_id` is now a `TINYINT`.
- `city_id` is now a `SMALLINT`.
- `country_id` is now a `SMALLINT`.
- `customer_id` is now a `SMALLINT`.
- `first_name`, `last_name` for `customer` table are now `CHAR` instead of `VARCHAR`.
- `customer` table now has `email` `CHAR(50)`.
- `create_date` on `customer` table is now `DATETIME` (to accommodate `last_update` `TIMESTAMP`).
- `customer` table has a new `ON INSERT` trigger that enforces `create_date` column being set to `NOW()`.
- `film_id` is now `SMALLINT`.
- `film.description` now has `DEFAULT NULL`.
- `film.release_year` added with type `YEAR`.
- `film.language_id` and `film.original_language_id` added along with `language` table. For foreign films that may have been subtitled. `original_language_id` can be `NULL`, `language_id` is `NOT NULL`.
- `film.length` is now `SMALLINT`.
- `film.category_id` column removed.
- New table: `film_category`; allows for multiple categories per film.
- `film_text.category_id` column removed.
- `inventory_id` is now `MEDIUMINT`.
- `payment_id` is now `SMALLINT`.
- `payment.payment_date` is now `DATETIME`.
- Trigger added to `payment` table to enforce that `payment_date` is set to `NOW()` upon `INSERT`.
- `rental.rent_date` is now `rental.rental_date` and is now `DATETIME`.
- Trigger added to `rental` table to enforce that `rental_date` is set to `NOW()` upon `INSERT`.
- `staff_id` is now `TINYINT`.
- `staff.email` added (`VARCHAR(50)`).

- `staff.username` added (`VARCHAR(16)`).
- `store_id` is now `TINYINT`.
- `film_list` view updated to handle new `film_category` table.
- `nicer_but_slower_film_list` view updated to handle new `film_category` table.